

Specification Data Sheet
Double Block & Vent Gas Safety Shutoff Valve Systems
Series T4100C, T4150C, T4200C

Customer: _____ Inquiry /P.O. _____

Location: _____ Quantity: _____

- Model Number:** T4100C One Inch Cast Steel Body with 3/4" Vent
 T4150C One & half Inch Cast Steel Body with 3/4" Vent
 T4200C Two Inch Cast Steel Body with 1" Vent
- Agency Approval:** Factory Mutual No approval required
- End Connection Type:** Spigot End Butt Weld Socketweld*
 ANSI Class 150# Flanges* MNPT* (schedule 80 only)
- Pipe Schedule:** Schedule 40 Schedule 80
- Flow Direction:** Right to Left Left to Right
- Valve Seal Material:** Buna-N (Standard) Viton (Consult Factory)*
- Actuator:** Pneumatic
- Failure Position:** Fail Closed Fail in Last Position (Non-FM approved)
- Solenoid Coil Voltage:** 110VAC 220VAC
 125VDC 48VDC 24VDC 12VDC
 Special Voltage (Consult Factory, Non-FM Approved)
- Limit Switch Type:** SPDT DPDT (must be externally mounted)
- Filter Regulator:** No (Standard) Yes* (Includes Pressure Gauge)
- Junction Box:** No (Standard) Yes* (Consult Factory, Non-FM approved)
- Auxiliary Limit Switch:** Open Limit Switch* Inlet POC Switch* (T4150C, T4200C only)
- External Switches:** Externally mounted* (Applies to SPDT Only)
- Hazardous Area Classification:** Non Hazardous (Nema 4)
 Class 1 Division 2* (Nema 7)
 Class 1 Division 1*

* Price Adder

Notes:

