



SIZE	A ^H	B ^H	D ^H	E ^H	F ^H	G ^H	H ^H
01.50	6.50 [165.12]	6.28 [159.51]	7.21 [183.12]	1.25 [31.82]	0.62 [15.72]	3.88 [98.62]	5.00 [127.02]
02.00	7.50 [190.51]	7.28 [184.91]	8.21 [208.51]	1.88 [47.82]	0.75 [19.12]	4.75 [120.71]	6.00 [152.41]

* RECOMMENDED SPARE PARTS

ITEM	DESCRIPTION	MATERIAL	QTY.
1	BODY, FLANGED	C.I. A-126, CL. B	1
2	BONNET	C.I. A-126, CL. B	1
3	COMPRESSOR	C.I. A-126, CL. B	1
* 4	DIAPHRAGM	-	1
5	BUSHING, NON-SEALED	BRASS B-21, GR. C48500	1
6	HANDWHEEL	C.I. A-48, CL. 30	1
7	SPINDLE, VALVE	CAR. STL. A-108, GR. 12L14	1
8	EXTENSION, SPINDLE INDICATING	STN. STL. A-582, TYPE 303	1
9	INSERT	CAR. STL. A-109, GR. 12L14	1
10	PIN, SPIROL	STN. STL. TYPE 302	1
11	MASHER, SHIM	POLYETHYLENE	AR
12	BEARING, THRUST NEEDLE	CAR. STL.	1
13	BEARING, THRUST RACE	CAR. STL.	2
14	SCREW, SET HEX. SDC.	ALLOY STEEL F-912	2
15	FITTING, LUBE	-	1
16	SCREW, HEX HD. CAP	CAR. STL. A-307	4
17	NUT, HEX.	CAR. STL. A-563, GR. A	4
18	CAPSEAL	BRASS B-36, ALLDY C26000	1
19	LOCKNUT, HEX.	STN. STL.	1
20	EXTENSION, SPINDLE ADJ. TRAVEL	STN. STL. A-582, TYPE 303	1
21	SPACER	STN. STL. A-582, TYPE 303	1
* 22	COLLAR, SEAL	BRASS B-16, C36000 HD2	1
* 23	O-RING DASH NO. 111	BUNA-N	1
* 24	BUSHING SEALED	BRASS B-21, GR. C48500	1
* 25	O-RING DASH NO. 216	BUNA-N	1
26	PLUG, V-NOTCH VENT 1/8" NPT	STN. STL. TYPE 304	1
* 27	O-RING DASH NO. 020	BUNA-N	1
28	SPACER	STL. A-108, GR. 12L14	1
29	PIN, SPIROL	STN. STL. TYPE 302	1

NOTES:
1. VALVE IS BI-DIRECTIONAL (NO FLOW ARROW).

UNLESS OTHERWISE SPECIFIED, DIMENSIONS NOT SHOWN IN BRACKETS () ARE IN INCHES. DIMENSIONS SHOWN IN BRACKETS () ARE IN MILLIMETERS.

ENGAD VALVES ORDER: -	ITEM: -	THIRD ANGLE PROJECTION	DATE: 10/20/14	BY: STRAIGHTWAY	VALVE ASSEMBLY	DATE: 10/20/14	BY: STRAIGHTWAY	DATE: 10/20/14	BY: STRAIGHTWAY
FIGURE NO.: -			CHKD: 10/20/14	10/20/14	STD				
CUSTOMER: -			ALL DIMENSIONS SHOWN ON THIS DRAWING ARE FOR REFERENCE ONLY.						
CUSTOMER P.O.: -			APPROV: 10/20/14	STD		MASTER CNG: 004700-171/C	ENG: 15829	ISSUED BY: -	DATE: -



Engineering Office
SHEET 1 REV 1